

Single Phase String Inverter **X1-Mini**



***Small Inverter
Big Performance***



Low Start-Up
Voltage



High
Efficiency



Small &
Lightweight



IP65
Rated

X1-0.7-S / X1-1.1-S / X1-1.5-S / X1-2.0-S

The SolaX X1 Mini range of inverters are designed and engineered for small PV arrays. With a start-up voltage of 65V and a maximum efficiency of 97.1%, the X1 Mini promises unrivalled performance, allowing you to harvest the maximum amount of energy possible from your PV system.





X1-MINI (SINGLE PHASE)

	X1-0.7	X1-1.1	X1-1.5	X1-2.0
INPUT (DC)				
Max.PV array power [Wp]	840	1250	1650	2200
Max.DC voltage [V]	400	400	400	400
Nominal DC operating voltage [V]	360	360	360	360
Max. input current [A]	10	10	10	10
Max. short circuit current [A]	12	12	12	12
MPPT voltage range[V]	55-380	55-380	55-380	55-380
Start operating voltage[V]	70	70	70	70
No. of MPP trackers	1	1	1	1
Strings per MPP tracker	1	1	1	1
OUTPUT AC				
Nominal AC power [VA]	700	1100	1500	2000
Max. AC power [VA]	700	1100	1500	2000
Nominal grid voltage(AC voltage range) [V]		220/230/240; 180~280		
Nominal grid frequency/range [Hz]		50/60; ±5		
Nominal AC current [A]	3.04	4.78	6.52	8.70
Max. AC current [A]	3.5	5.5	7.5	9.5
Displacement power factor		0.8 leading ~ 0.8 lagging		
THDi, rated power [%]		<3		
EFFICIENCY				
MPPT efficiency [%]		99.9		
Euro efficiency [%]	95	95.5	96	96.5
Max. efficiency [%]		97.1		
POWER CONSUMPTION				
Standby consumption (Night) [W]		<1		
STANDARD				
Over voltage protection		YES		
Over current protection		YES		
DC isolation impedance monitoring		YES		
Ground fault current monitoring		YES		
DC injection monitoring		YES		
RCD protection		YES		
Safety		IEC62109-1/-2		
EMC		EN61000-6-1;EN61000-6-2;EN61000-6-3;EN61000-3-2;EN61000-3-3		
Certification		G98; AS4777; VDE4105; EN50549; CEI0-21		
ENVIRONMENT LIMIT				
Degree of protection(according to IEC60529)		IP65		
Operating temperature range [°C]		-25~+60(de-rating at 45)		
Max. operation altitude [m]		2000		
Humidity [%]		0~100 (condensation)		
Storage temperature [°C]		-25~+60		
Typical noise emission [dB]		<25		
DIMENSION AND WEIGHT				
Dimensions(WxHxD) [mm]		267*328*116		
Weight[kg]		6		
Cooling concept		Natural		
Topology		Non-isolated		
Communication interfaces		Pocket WiFi(optional)/Pocket LAN(optional)/Pocket GPRS(optional)/Meter(optional)/RS485/DRM/USB-Upgrade		
LCD display		Yes		
Standard warranty [years]		5-10		